

FDR 19" ODF Rack Mount

Standard

ODF Rack Mount Patch Panel is ideal for installations on the standard 19" racks.

Features

- ▶ Top quality steel with electrostatic painted ensures the strong body and pleasing appearance;
- ▶ For standard 19" racks use (other rack width options available on request);
- ▶ Front rack mount brackets work with most network cabinets.
- ▶ Removable front door with designation labels.
- ▶ Vertical cable guides on exit side allow for managed routing and protection of the fiber exiting the panel.
- ▶ Multi-functions Works with all CONTECH (not just for splicing & terminating, also with options for splitters or fiber storage)
- ▶ Protected patch panel offers secure environment for adapters, patch cords and pigtails;
- ▶ Adaptable adapter types: FC, SC, ST simplex adapters and LC duplex adapters;

Operation conditions

Temperatures: -5C – 60C
 Humidity: 90% at 30C
 Air Pressure: 70kPa - 106kPa

Dimensions and Capacity

Height: Depends on the capacity
 Width: for 19" or 23" rack mount
 Depth: 300mm
 Capacity: For Series A modules: 1 - 8
 Recommended capacity for fiber terminations: 12 - 96
 (A1 modules are recommended which terminates 12 ports per module, capacity doubles when using LC adapters)



P/N: CS-FDR19T12B-48



P/N: CS-FDR19T12B-48



P/N: CS-FDR19T12B-24



P/N: CS-FDR19T12B-12



P/N: CS-FDR19T12B-BLU



P/N: CS-FDR19T12B-GR

