

CAT-6 RJ45 UTP Keystone Jacks

Application

CAT-6 RJ45 Un-Shielded Keystone Jacks for transmission of digital and analogue voice, video and data signals. Suitable for all Class D applications respectively Class E Channels in accordance with ISO/IEC 11801, EN 50173-1 and TIA/EIA 568-B.2-10.

Features

- ▶ Tool-less termination and Re-usable
- ▶ Supports Gigabit Ethernet over Un-shielded copper to a full 100m up to 250MHz
- ▶ Compatible both T568A and T568B wiring schemes.
- ▶ Compatible with all Keystone mounting wallplates & Adoptar
- ▶ Integral shutter increased dust protection and protects jacks in the patch panel
- ▶ Accepts both solid conductors from AWG 24 to 22 and stranded conductors

Physical Specifications

Insertion Life:	750 Mating Cycles with Fcc Compliant 8P Plug.
Contact Force:	100 Grams with Fcc Compliant 8P Plug.
Plug Retention Force:	11 Lbf Min.
Durability:	30 Termination Cycles.
Contact Compatibility:	Accommodates 22 To 24 Awg Solid.
Flame rating:	UL 94 V-0
Operating Temperature Range:	-10 C To 60 C.
Storage Temperature Range:	- 40° C Up To + 70° C
Humidity:	10%~90%Rh
Connector Type:	Only Accept RJ-45 8P8C Plug

Electrical Specifications

Insulation Resistance:	500 MΩ.
Dielectric Withstanding Voltage:	1000 V Ac.
Dc Current Rating:	1.5 Amps.
Dc Resistance:	0.1Ω.
Contact Resistance:	20MΩ.

Standard

Cat./Class: Cat.6 / Class E
Standards: IEC 60603-7-4 (Cat.6 unshielded, 250 MHz)
 ISO/IEC 11801:2002/ Amd.2:2010
 EN 50173-1:2011
 TIA/EIA 568-B.2-10:2008
Compliance: UL-listed, Intertek (ETL) & EC Delta Certified



CAT-6 RJ45 UTP
Keystone Jacks



Order Information

Part No	Type of Item	Type of Class	Type of Jacket	Standard Quantity
CS-6XU8PS-WH	Toolless Keystone Jack	CAT-6	UTP	1,8 & 24 Pieces - Packet