

FC – FC/LC/SC Duplex Fiber Optic Assemblies/Patch Cord

Features and Benefits

Applications:



- Data Centers: ODF-to-ODF.
- Telecom Networks/FTTH (Fiber-to-the-Home).
- Enterprise Networks: LAN/WAN connectivity.
- CATV & Broadcasting: High-speed signal transmission.

Key Features:

- Connector Type: FC (Ferrule Connector) – a circular screw-type fitting with a 2.5mm ferrule.
- A duplex patch cord consists of two fiber cables (typically single-mode or multimode) with A side FC B side FC/LC/SC optional connectors on both ends.
- Flexible design options: Choice of materials for strength elements and fiber properties dependent on application requirements.

Standard:

- TIA/EIA-568-C.3,
- IEC 61754-20,
- UL94V-0 for flame resistance.
- IEC 60332-1,2
- RoHS



15

Physical & Mechanical Specifications

| | |
|----------------------------------|---|
| Connector Type A/B | A: FC-UPC / B: FC/LC/SC -UPC Duplex |
| Connector Housing /Ferrule | A: FC Stainless Steel / B: LC/SC ABS/Ceramic Zirconia |
| Cable Assembly Type | 2 Fibers Tight-Buffered -Zipcord |
| Strength Potation | Aramid yarn (Kevlar®) |
| Outer Jacket Type & OD. | LSZH – 2.0mm |
| Connector Durability | 1000 times |
| Tensile Strength | (Long-term ≥90 N /Short-term: ≥150 N) |
| Min. Bend Radius (Optical Fiber) | 10mm |
| Min. Bend Radius (Fiber Cable) | 20/10D (Dynamic/Static) |
| Operating Temperature | -10 to 70°C (14 to 158°F) |
| Storage Temperature | -20 to 70°C (-4 to 158°F) |

Optical Characteristics

| | |
|----------------|----------------------------------|
| Fiber Type | Single Mode (SM) |
| Core Type | ITU-T G.652.D-G.657.A1 - 9/125µm |
| Wavelength | 1310 nm / 1550 nm |
| Insertion Loss | ≤0.3dB |
| Return Loss | ≥50dB-UPC/≥60dB-APC |

Ordering Information

| Fiber Type | SMF-28® Ultra ITU-T G.652.D | SMF-28® Ultra ITU-T G.652.D | SMF-28® Ultra ITU-T G.652.D | SMF-28® Ultra ITU-T G.657.A1 |
|-----------------|--|--|--|--|
| Jacket Color | Yellow | Yellow | Yellow | Yellow |
| Part No. | CS-FP2D52D-FC-FC-XX | CS-FP2D52D-FC-LC-XX | CS-FP2D52D-FC-SC-XX | CS-FP2D57A-FC-APC-FC-APC-XX |
| Optional Length | 01M, 02M, 03M, 06M 10M, 15M, 20M, 30M |