

2U Rack Mount MPO-MTP Modular Slide Drawer High Density Fiber Patch Panel

Features and Benefits

Applications:

- Data Centers: Optimized for high-density fiber deployments, ensuring minimal signal loss and efficient space utilization, include backbone-network connections, cross-connects, and interconnects in structured cabling systems compliant with TIA-942 and EN 50173-5 standards
- Telecommunications: Used for trunk fiber termination and cross-connect applications in central offices or telecom rooms. The enclosures facilitate plug-and-play performance with pre-terminated MPO/MTP cassettes, reducing installation time and improving reliability
- Enterprise Networks: Enhances structured cabling infrastructure in large buildings or campus backbones. The enclosures support modular upgrades, allowing flexibility in mixing singlemode and multimode cassettes based on network



Key Features:

- The 2U Unloaded Slide Drawer design, accepts 24 x MPO/MTP cassettes.
- Designed for 40G/100G networks with low insertion loss.
- Pre-terminated MPO/MTP cassettes eliminate on-site splicing, enabling quick network rollouts.
- The tool-less cassette design simplifies maintenance and reconfiguration for future upgrades
- Quick deployments in enterprise networks or data centers.
- Easy for management and operation.
- Supports up to 288F cores 144 LC Duplex in 2U space..
- Cassettes: MPO Connector /LC Adapter and MM ClearCurve® & SM SMF-28® Ultra Fiber.
- Support Migration from 10G to 40G/100G Ethernet and Beyond.



Standard:

- EIA 19" rack
- TIA942-A, TIA 568C.3
- GR-1435-CORE
- RoHS

Physical Specifications

Enclosure Structure:

Enclosure Type: 2U UHD MPO/MTP-LC Patch Panel

Capacity: MPO/MTP 1x12F - 24 Modular Cassettes

Cable Entry Direction: Rear Entry

Material: CRS Cold-Rolled Steel

Dimension: 177Hx482Wx455D mm

Color: Black

MPO/MTP® Cassette:

Modular Type: Pre-Terminated 12C x 06 LC (Duplex) Ports MPO/MTP Cassette

Fiber Type: Single-mode (G.652.D/G.657.A1)/Multimode (OM3/OM4/OM5)


Adapter (Front): LC (Duplex)

Adapter (Rear): MPO/MTP Female (1x12F)

Polarity: Type A & Type B

Insertion Loss: MPO/MTP ≤0.35dB, LC≤0.2dB

Return Loss: MPO/MTP ≥20dB, LC≥30dB (UPC polish)



Ordering Information

1U Enclosure Part No.	OM3 1 x12 Fibers 06/x LC Duplex, MPO/MTP Cassette	OM4 1 x12 Fibers 12/x LC Duplex, MPO/MTP Cassette	OM5 1 x 12 Fibers 12 x LC Duplex, MPO/MTP Cassette	OS2 1 x 12 Fibers 12 x LC Duplex, MPO/MTP Cassette
CS-RM2FSR24M-XX	CS-MPO-M3-DLC112 CS-MTP-M3-DLC112	CS-MPO-M4-DLC112 CS-MTP-M4-DLC112	CS-MPO-M5-DLC112 CS-MTP-M5-DLC112	CS-MPO-S2-DLC212 CS-MTP-S2-DLC212